

0060035



**SAERTEX®**  
Reinforcing Your Ideas!

## TECHNICAL DATASHEET

SAP No. 30007630 Article Description X-E-444g/m<sup>2</sup>-1270mm

Textile Structure 7004131

SAERTEX®

### ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
4	45 °	217 g/m <sup>2</sup>	+/- 5,0 %	E-glass
3	90 °	2 g/m <sup>2</sup>	+/- 5,0 %	E-glass
2	0 °	2 g/m <sup>2</sup>	+/- 5,0 %	E-glass
1	-45 °	217 g/m <sup>2</sup>	+/- 5,0 %	E-glass
Stitching		6 g/m <sup>2</sup>	+/- 1 g/m <sup>2</sup>	synthetic

Fiber input can be determined individually

### FURTHER CHARACTERISTICS

Gauge	5,0	Stitching pattern	warp	Width (nominal)	1270 mm
Stitch length	3,00 mm	Total tolerance	+/- 5,2 %	Total areal weight	444 g/m <sup>2</sup>

Labelling (Standard) Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard) Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage With original packaging: No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.

SAERTEX GmbH & Co. KG has been certified in accordance with ISO 9001:2015 and has been awarded the 2020 Eco-Profit Award. The SAERTEX GmbH & Co. KG has its own DNV GL certified laboratory.

REINFORCING YOUR IDEAS